

Webhook Configuration API Sample Document

This document outlines the usage of the Webhook Configuration API, including request formats, endpoints, and example payloads.

Base URL

```
https://api.example.com/webhooks
```

1. Create Webhook

Creates a new webhook with specified configuration.

```
POST /webhooks
Content-Type: application/json
```

Request Body Example:

```
{
  "url": "https://yourapp.com/webhook",
  "events": ["user.created", "payment.success"],
  "active": true,
  "secret": "abc123"
}
```

Response Example:

```
{
  "id": "wh_12345678",
  "url": "https://yourapp.com/webhook",
  "events": ["user.created", "payment.success"],
  "active": true,
  "created_at": "2024-06-22T10:15:36Z"
}
```

2. List Webhooks

```
GET /webhooks
```

Response Example:

```
[
  {
    "id": "wh_12345678",
    "url": "https://yourapp.com/webhook",
    "events": ["user.created"],
    "active": true
  },
  {
    "id": "wh_87654321",
    "url": "https://another.com/notify",
    "events": ["order.completed"],
    "active": false
  }
]
```

3. Update Webhook

```
PATCH /webhooks/{id}
Content-Type: application/json
```

Request Body Example:

```
{
  "active": false
}
```

4. Delete Webhook

```
DELETE /webhooks/{id}
```

Field Description

Field	Type	Description
id	string	Webhook identifier
url	string	Endpoint to receive webhook payloads
events	array	Subscribed event(s) for webhook
active	boolean	Status of the webhook
secret	string	Optional verification secret
created_at	string	Timestamp of creation

Supported Events

```
user.created
```

```
payment.success
```

```
order.completed
```

